



Sicad S.p.A.

Via Caduti della Liberazione, 57
21040 Uboldo (VA) – Italia
Tel: +39 02 964121 Fax: +39 02 96412294
Web: www.eurocel.it

PRODUCT INFORMATION

EUROCEL 721 PPDA

DESCRIPTION

Double sided adhesive tape.

PRODUCT DATA

Backing	0.050 mm OPP; transparent
Adhesive	Synthetic rubber and resins
Liner	Double sided siliconized paper; brown

	Unit	Value	Method
Total thickness (without Liner)	mm	0.115	PSTC 133
Adhesion to steel	N/25mm	Int: 25 – Ext: 20	PSTC 101
Tensile strength MD	N/25mm	50	PSTC 131
Elongation at break	%	600	PSTC 131
Temp. Resistance	°C	60°C	=

APPLICATION

Double sided filmic carpet tape for many industrial applications, suitable even for fixing samples, general items and felt pads. Easy to use.

Features	Benefits	
Synthetic rubber and resins	✓ High tack and high adhesion level both sides	✓ Good adhesion on different surfaces
OPP backing	✓ High elongation ✓ Well adaptable on different shapes	✓ Hand tearable ✓ Easy use

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

DS010EN_REV02_721PPDA

Società Italiana Cellophane Adesivo
P.I. e C.F. IT 00220060123
Iscrizione R.E.A. Varese n. 129175
Reg. Imprese Varese n. 00220060123
Capitale Sociale € 15.000.000 i.v.